



AT-LP1240USB

direct-drive professional DJ turntable



AT-LP1240USB

The **AT-LP1240USB** is built to deliver exceptional music reproduction even under the most demanding conditions. It utilizes a powerful direct-drive 16-pole, three-phase motor for unwavering speed stability along with easy back-cueing, forward and reverse play and quiet operation at 33-1/3, 45 or 78 RPM. The turntable features an S-shaped tone arm with adjustable tracking force (counterweight) and anti-skate adjustment and a removable universal cartridge mount (cartridge available separately). The tone arm has locking height adjustment to dial in the vertical tracking angle (VTA), an important feature for achieving the most accurate-possible record playback.

The **AT-LP1240USB** comes with numerous additional DJ-friendly features including a damped cast-aluminium platter with stroboscopic speed markings and slip mat, an illuminated speed indicator and adjustable pitch control, a start/stop button, a removable stylus target light, a dedicated tone arm grounding lug, a hydraulically-damped lift lever and a locking tone arm rest that keeps the arm and cartridge in place during transport.

The **AT-LP1240USB** is also perfect for home users. Its sleek, elegant gloss-black and silver design fits into any stereo music or home entertainment system, and its built-in switchable phono preamp enables it to be used with a wide variety of receivers, powered speakers and other A/V components.

EAN: 5055145747599

Available: September 2012

Specifications*:

Type:	3-speed, fully manual operation
Motor:	16-pole, 3-phase, brushless DC motor
Drive Method:	Direct drive
Speeds:	33-1/3 RPM, 45 RPM, 78 RPM
Turntable Platter:	332 mm dia. die-cast aluminium
Starting Torque:	>4.5 kgf.cm
Braking System:	Electronic brake
Wow and Flutter:	< 0.1% WRMS (JIS WTD) with 33 RPM
Signal-to-Noise Ratio:	> 55 dB (DIN-B)
Output Level:	Pre-amp «PHONO»: 2.5 mV nominal at 1 kHz, 5 cm/sec (HP-4005) Pre-amp «LINE»: 150 mV nominal at 1 kHz, 5 cm/sec (HP-4005)
USB Function:	A/D, D/A - 16 bit 44.1 kHz or 48 kHz USB selectable; Computer interface - USB 1.1 Compliant Windows XP or above or MAC OSX or above
Dimensions:	450.0 mm W x 353.0 mm D x 166.5 mm H
Weight:	12.5 kg
Accessories Included:	Slip mat; dust cover; platter; 45 RPM adapter; counterweight; headshell; power cord; USB cable; dual RCA (female) to 1/8" (3.5 mm) mini-plug (male) stereo adapter cable; dual RCA (female) to 1/8" (3.5 mm) mini-plug (female) stereo adapter cable; dual RCA (male) cable with integrated ground wire; stylus target light; Audacity software (CD)

* Specifications are subject to change without notice.

 **audio-technica**
always listening

Audio-Technica Limited, Technica House, Unit 5, Millennium Way, Leeds LS11 5AL England
Audio-Technica SAS, 11 rue des Pyramides, 75001 Paris, France
Audio-Technica Niederlassung Deutschland, Lorenz-Schott-Str.5, D-55252 Mainz-Kastel, Germany
Audio-Technica Central Europe Ltd, Fogado u. 3, Budapest 1107, Hungary
©2012 Audio-Technica, www.audio-technica.com